

iLOFT

by FERMAX

VIDEO DOOR ENTRY SYSTEM



ESSENTIAL DESIGN

Compact, extra slim and light. Fastened to the wall. Beauty sustained by high performance electronics make iLOFT the designer's choice.

With iLOFT comes the perfect balance between communication and security needs in the home and the elegance and integration required in the most cutting-edge architecture.

SINGULAR DETAILS



Transparent polycarbonate cover.



Colour 3.5" TFT screen.



Audio output.



Multi-function pushbuttons.






A simple and easy OSD menu, available in some versions, allows any user to make the most of the iLOFT functionalities.



HANDS-FREE OPERATION

Maximum simplicity and convenience.

When a call is received from the video door entry panel, the image comes up automatically.

Press  once to speak and hold a conversation with the visitor with no need of a handset. Press  to open the door. Communication ends after 90 seconds or when  is pressed again.

Includes activation of 2 additional functions for volume control and brightness-contrast-colour settings as standard.



ACCESSORIES

Decorative frame made in bevelled glass acts as aesthetic complement and lets you cover gaps left by other equipment.

Colours cover.

Customize each monitor.

-  Silver
-  Black
-  Gold



DIMENSIONS / INSTALLATION

Monitor emerges 13 mm from the wall once embedded.

Monitor:	131 x 197 x 59
Fermax flush box:	108 x 158 x 45
Standard flush box:	114 x 174 x 50
Decorative frame:	189 x 256 x 60



Measures in mm. (W)x(H)x(D)