

iLOFT

by FERMAX

VIDEO DOOR ENTRY SYSTEM SURFACE



ESSENTIAL DESIGN

Compact, extra slim and light. Beauty sustained by high performance electronics make iLOFT the designer's choice. Wall fitted, it requires no building works and can be installed onto any kind of wall.

With iLOFT comes the perfect balance between communication and security needs in the building and the elegance and integration required in the most cutting-edge architecture.




SINGULAR DETAILS



Transparent polycarbonate cover.




Colour 3.5" TFT screen.



Audio output.



Multi-function pushbuttons.



A simple and easy OSD menu, available in some versions, allows any user to make the most of the iLOFT functionalities.






Surface-mounted installation.

HANDS-FREE OPERATION

Maximum simplicity and convenience.

When a call is received from the video door entry panel, the image comes up automatically.

Press  once to speak and hold a conversation with the visitor with no need of a handset. Press  to open the door. Communication ends after 90 seconds or when  is pressed again.

Includes activation of 2 additional functions for volume control and brightness-contrast-colour settings as standard.



High quality communication

Built-in digital audio technology ensures high quality and interface-free two way communication.

DIMENSIONS / INSTALLATION

Flush mounted installation
Monitor 131x197x36

Measures in mm. (W)x(H)x(D)

